



GPGrid2BX is a geogrid made from high-tenacity PET yarns that providing high tensile strength at low elongation which are covered PVC coating.

Properties	Unit	20/20	35/35	60/60	90/90	130/130	200/200
Mechanical properties							
[EN ISO 10319]							
Strength characteristic							
● MD	kN/m	20	35	60	90	130	200
● CD	kN/m	20	35	60	90	130	200
Elongation at Strength characteristic							
(Tolerance %10±)							
Mesh Size							
● MD	mm	35	35	35	33	32	28
● CD	mm	25	25	25	25	22	20
(Tolerance 5±mm)							
Roll Size							
● Roll Width(10±cm)	m	5.25	5.25	5.25	5.25	5.25	5.25
● Roll Length	m	100	100	100	50	50	50

The values given are average values obtained in our laboratories and in accredited testing institutes. The information given in this datasheet is to the best of our knowledge true and correct. However new research results and practical experience can make revisions necessary. The right is reserved to make changes without notice at any time. No guarantee or liability can be drawn from the information mentioned herein.

C4-01-01-12

Factory: 32 Km, Lahore Sheikhpura Road, Lahore.

Head Office: 8, Block T, Phase 2 Defence Lalak Jan Chowk.

Regional Office: 16-Badar Block,said Purstop, Multan Road, Lahore.

Contact: 04235707642 - 43  0300-8489737, 0321-8489737

PETROSEALE@GMAIL.COM